

Lifestyle RFPT Wireless Programmable Room Thermostat



The Drayton wireless programmable thermostat systems have been designed to make your life easier.

Installation couldn't be simpler thanks to the reliable wireless technology and well loved familiar features. The Lifestyle RFPT has a range of features to make your, and your customer's life, much easier.

- · Simple installation
- · Standard backplate for SCR
- · No wiring, no plasterwork to chase out
- No re-decoration
- · Positioning not restricted by cable runs

Getting technical

	Lifestyle RFPT	LP SCR Receiver
Power supply:	2 X 1.5V IEC LR6(AA) alkaline batteries	230V a.c. 50Hz
Switch type and rating:	N/A	SPDT (voltage free) 2(1)A 230V a.c. or 24V a.c/d.c
Wiring:	No wiring required	Designed for fixed wiring only, to comply with current IET wiring regulations (BS7671).
Mounting:	Suitable for surface or conduit box mounting	Industry standard wall plate
Battery life:	2 years typical	N/A
Ambient temperature:	Operating 0°C to 40°C Storage – 20°C to 55°C	
Ambient humidity (non condensing):	Operating 25% to 90% Storage 15% to 95%	
Temperature range:	5°C - 32°C	
Temperature resolution:	0.5°C	
Control accuracy:	+ 0.5K @ 20°C	
Timing resolution:	1 minute	
Ball pressure test:	75°C	
Pollution degree:	2	
Protection level:	IP30	
Software class:	А	
Radio frequency:	433 MHz	
Radio signal range:	30m typically. The range may be affected by the composition / density and number of walls between the thermostat and receiver.	
Energy class:	IV = 2% (Acc. EU 811/2013, 812/2013, 813/2013, 814/2013)	
Relevant EC directives:	2014/53/EU Radio Equipment Directive 2011/65/EU RoHS Directive	
Applied standards:	EN60730-1; EN60730-2-7; EN60730-2-9 EN 300 220-2; EN 301 489-3	

Product	Part No.
Lifestyle RFPT	THD22120

Made for simplicity

- Easy temperature override
- 4 button programming
- Memory saver function
- Auto summer/winter time updates
- Pre-set clock
- 3 built-in standard programmes
- Large LCD display
- Part L compliant

Made for flexibility


- On/off load compensation
- 24hr, 5/2 day or7 day programmes
- Holiday mode
- 12 or 24 hour clock
- Intelligent delayed start option
- Up to 6 time/ temperature events per day
- Suitable for combi boilers, hydronic underfloor and zoning


How we measure up

Lifestyle RFPT Programmer



SCR Receiver





draytoncontrols.co.uk

Customer & Technical Support: 0333 6000 622

D131-1

In accordance with our continuous improvement procedures, we reserve the right to change design features and specifications without prior notification. The Data contained in this document is for guidance only. Drayton accepts no liability for any consequential losses, injury or damage resulting from the use of this document or the information contained within.









