

Drayton

by Schneider Electric



				TRV Keymark declared flowrates @ pre-setting positions for Drayton Auto Balancing (AFC) Valves															
				FO	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
Valve Type	Series	Form	Nominal Size	(qm N)	(qm s)	(qm s)	(qm s)	(qm s)	(qm s)	(qm s)	(qm s)	(qm s)	(qm s)	(qm s)	(qm s)	(qm s)	(qm s)	(qm s)	(qm s)
AFC 15 mm Angle	GB	Angle	DN 15	94 kg/h	78 kg/h	74 kg/h	69 kg/h	64 kg/h	59 kg/h	54 kg/h	48 kg/h	42 kg/h	35 kg/h	30 kg/h	25 kg/h	21 kg/h	17 kg/h	15 kg/h	13 kg/h
AFC 15 mm Straight	GB	Straight	DN 15	94 kg/h	78 kg/h	74 kg/h	69 kg/h	64 kg/h	59 kg/h	54 kg/h	48 kg/h	42 kg/h	35 kg/h	30 kg/h	25 kg/h	21 kg/h	17 kg/h	15 kg/h	13 kg/h
				Tolerance															
				+/- 10 %	+/- 10 %	+/- 10 %	+/- 10 %	+/- 10 %	+/- 10 %	+/- 12 %	+/- 12 %	+/- 15 %	+/- 15 %	+/- 17 %	+/- 20 %	+/- 22 %	+/- 25 %	+/- 27 %	+/- 30 %

Drayton

oreg ①