Digistat+2/+2Si Digistat+3/+3st

Wired Programmable **Room Thermostats**





Mon Tue Wed Thu Fri Sat Sun





BUILT FOR RELIABILITY

The Digistat programmable thermostat systems offer accurate time and temperature control in one handy device. The traditional wired device provides good old familiarity and reliability; simply install, set, and leave it to work its magic. It's fact, heating controls can save up to 52% on heating bills.*

- Time and temperature control
- Simple installation
- Flexible programming
- Helps save homeowners up to 52% on bills



BUILT TO BE VERSATILE

Both Digistat+2 and +3 have a range of features to make yours, and your customer's

FLEXIBLE FEATURES

- On/off load compensation
- 24hr, 5/2 day or 7 day programmes (Digistat +3)
- Battery or mains powered options

- Intelligent delayed start option
- Up to 6 time/temperature events per day
- Suitable for combi boilers, hydronic underfloor

MAKING LIFE EASY

- Easy temperature override
- 4 button programming
- Memory saver function
- Auto summer/winter time updates
- Pre-set clock
- 3 built-in standard programmes
- Large LCD display

NEW Service interval features

- Flexible service interval mode (reminder, reduced comfort or off)
- Adjustable warning period
- Adjustable service period
- Visual indication on LCD
- Selectable boost feature
- Selectable audible alarm
- Reset by installer selectable 4-digit code

HOW DO WE MEASURE UP? Digistat+2/+3












Wiring:








Basic Boiler with Zone Valve







WHAT'S THE DIFFERENCE BETWEEN A **DIGISTAT+2 AND +3?**

Digistat+2 allows you to set the same programme for every day of the week. Digistat+3 gives you the option of setting a different programme for each day, or different programmes for weekends and week days.

PART NUMBERS

Products in range	Part No.	Si Part No.
Digistat+3 (Battery) 7 day/5-2 day	22083	22104
Digistat+2 (Battery) 24Hr	22084	22102
Digistat+3 (Mains) 7 day/5-2 day	22087	22105
Digistat+2 (Mains) 24Hr	22088	22103

TECHNICAL DATA

TECHNICAL DATA			
Model:	Digistat+2/+3 (Battery)	Digistat+2/+3 (Mains)	
Power supply:	2 X I.5V IEC LR6(AA) alkaline batteries	230V a.c. 50Hz	
Switch type and rating:	SPDT I6(2)A 230V a.c. Volt free		
Min. recommended current:	I0mA@24V a.c. (inductive)		
Wiring:	Designed for fixed wiring only, to comply with current IET wiring regulations (BS767I).		
Mounting:	Suitable for surface or conduit box mounting		
Battery life:	2 years typical		
Ambient temperature:	Operating 0°C to 40°C Storage – 20°C to 55°C		
Ambient humidity (non condensing):	Operating 25% to 90% Storage I5% to 95%		
Temperature range:	5°C to 32°C		
Temperature resolution:	0.5°C		
Control accuracy:	+ 0.5K @ 20°C		
Timing resolution:	l minute		
Ball pressure test:	75°C		
Pollution degree:	2		
Protection level:	IP30		
Software class:	A		
Energy class:	IV = 2% (Acc. EU 8II/20I3, 8I2/20I3, 8I3/20I3, 8I4/20I3)		
Relevant EC directives:	2014/35/EU Low Voltage Directive 2014/30/EU Electromagnetic Compatibility Directive 2006/66/EC Batteries Directive 2011/65/EU RoHS Directive		
Applied standards:	EN60730-I; EN60730-2-7; EN60730-2-9 EN 300 220-2		



9° NETWORK

Join our professional installer club today and benefit from extended guarantees, priority support and much more.

www.draytoncontrols.co.uk/9degrees







Customer Service Support: 0333 6000 622

www.draytoncontrols.co.uk | customer.care@draytoncontrols.co.uk



In accordance with our continuous improvement procedures, we reserve the right to change design features and specifications without prior notification. The Data contained in this document is for guidance only. Drayton accepts no liability for any consequential losses, injury or damage resulting from the use of this document or the information contained within.